

APPENDIX III

Modeling Information

Modeling Information

INTRODUCTION

In order to assess the impact of pollutants on surface water quality, the Division must often develop and apply water quality models. A water quality model is a simplified representation of the physical, chemical, and biological processes which occur in a water body. The type of model used is dependent on the purpose for which it is needed, the amount of information that is available or attainable for its development, and the degree of accuracy or reliability that is warranted. In most cases, the Division develops and applies a given model to predict the response of the system to a given set of inputs that reflect various management strategies. For example, water quality models such as QUAL2E or the Division's Level B model are used to predict what the instream dissolved oxygen concentration will be under various sets of NPDES wasteflows and discharge limits. The following sections briefly summarize the types of models used by the Division.

Oxygen-Consuming Waste Models

Several factors are considered when choosing an oxygen-consuming waste model including: the type of system (stream, lake, or estuary), whether one, two, or three dimensions are needed, the temporal resolution needed, and the type of data available. Many of the factors are related. For example, in streams, flow usually occurs in one direction and one can assume that a steady state model will result in adequate predictions. A steady state model is one in which the model inputs do not change over time. However, in open water estuaries, the tide and wind affect which way water moves, and they must often be represented by 2 or 3 dimensional models. In addition, the wind and tide can affect the model reaction rates, and therefore a dynamic model must be used rather than one which is steady state. The last factor, the amount of data available, dictates whether an empirical or calibrated model will be used. An empirical model is used when little water quality information is available for a given water body, and hydraulics and decay rates are estimated through the use of equations. For example, in North Carolina's empirical stream model (referred to as a Level B analysis) velocity is determined through a regression equation developed from North Carolina stream time-of-travel (TOT) studies which includes stream slope and flow estimates as independent variables. Stream slope can be measured from a topographic map, and flow is estimated at a given site by the U.S. Geological Survey. Therefore, the empirical model can be run without TOT information specific to a given stream since parameters are estimated through the use of information which can easily be obtained in the office environment. More information regarding the empirical dissolved oxygen model used by DEM can be found in the Instream Assessment Unit's Standard Operating Procedures Manual.

Field calibration of a BOD/DO model requires collection of a considerable amount of data. For example, in order to develop hydraulics equations specific to a given stream, TOT studies using rhodamine dye are recommended under at least two flow scenarios including one summer low flow period. In addition, during one summer low flow study, dissolved oxygen, temperature, long term BOD and nitrogen series data are collected. ~~Sediment oxygen demand (SOD) data may also be collected.~~ These data are then used to calibrate reaction rates specific to the stream. QUAL2E is the most commonly used calibrated DO/BOD model for streams in North Carolina. A copy of the model guidance can be obtained from EPA's Environmental Research Lab in Athens, Georgia, and further information on North Carolina's calibration procedures can be found in the Instream Assessment Unit's Standard Operating Procedures Manual.

Data collection for an estuary DO model is even more extensive. Since the system is multi-dimensional and not steady-state, many more data are needed. Dye is often injected into a system over a period of time, and the dye cloud is then followed for a period of time which may last for days. In addition, several tide gages may need to be set up. Due to the stratification which occurs in an estuary, depth integrated data must also be collected. Calibrated estuary models which have been used by DEM include WASP and GAEST. WASP is also supported by EPA, and a user manual may be obtained from them. You should note that both GAEST is a one dimensional and is not applicable to many of North Carolina's estuaries.

Lakes are rarely modeled for BOD. Tributary arms of lakes are modeled as slow-moving streams if it is clearly indicated that the flow goes in one direction at all times. Depending on the system, a one, two, or three dimensional model may be used. If a one dimensional model is needed, the modeler may choose the Level B (if little or no data), or QUAL2E. In multidimensional lake systems, WASP will be used.

The calibrated model will be more accurate than the empirical model since it is based on data collected specifically for a given stream in the State. However, it is much more expensive to develop a calibrated model. Not only do a number of staff spend several days to weeks collecting field data (sometimes having to wait months for appropriate conditions), but it also takes the modeling staff several months to develop and document the calibrated model. An empirical model can be developed and applied in a matter of hours. Therefore, due to resource constraints, the majority of the BOD/DO models developed in North Carolina are empirical.

Eutrophication Models

Eutrophication models are used to develop management strategies to control trophic response of a system to nutrient inputs (usually total phosphorus (TP) or total nitrogen (TN)). Nutrient management strategies are typically needed in areas which are sensitive to nutrient inputs due to long residence times, warm temperature, and adequate light penetration. These characteristics are found in deep slow moving streams, ponds, lakes, and estuaries. Modeling and insitu research are used to relate nutrient loading to the trophic response to the system allowing the manager to establish nutrient targets. Models which may be used include the Southeastern Lakes Model (Reckhow, 1987), Walker's Bathtub Model (Walker, 1981), QUAL2E, and WASP.

Once the nutrient targets are known, watershed nutrient budgets are developed to evaluate the relative nutrient loadings from various point and nonpoint sources. Land use data are obtained for the basin, and export coefficients based on literature values are applied to each land use. An export coefficient is an estimate of how many pounds of nutrient will runoff from each acre of land in a given year.

Toxics Modeling

Toxics modeling is done to determine chemical specific limits which will protect to the "no chronic" level in a completely mixed stream. The standards developed for the State of North Carolina are based on chronic criteria. These chemical specific toxics limits are developed through the use of mass balance models:

$$(C_{up})(Q_{up}) + (C_w)(Q_w) = (C_d)(Q_d) \text{ where}$$

C_{up} = concentration upstream

Q_{up} = flow upstream

C_w = concentration in wastewater
(known being solved for in WLA)

Q_w = wasteflow

C_d = concentration downstream

(set = to standard or criteria)

Q_d = flow downstream (= $Q_{up} + Q_w$)

When no data are available concerning the upstream concentration, it is assumed to be equal to zero. The upstream flow is the 7Q10 at the discharge point unless the parameter's standard is based on human health concerns, in which case the average flow is used.

REFERENCES CITED - MODELING APPENDIX

Reckhow, K. H., 1987. "A Cross-Sectional Analysis of Trophic State Relationships in Southeastern Lakes." Duke University School of Forestry and Environmental Studies, Durham, N.C.

Walker, W. W., Jr. 1981. "Empirical Methods for Predicting Eutrophication in Impoundments," Technical Report E-81-9, prepared by William W. Walker, Jr., Environmental Engineer, Concord, Mass., for the U.S. Army Engineer Waterways Experiment Station, CE, Vicksburg, Miss.

1. The first part of the document discusses the importance of maintaining accurate records of all transactions and activities. It emphasizes that this is essential for ensuring transparency and accountability in the organization's operations.

2. The second part of the document outlines the various methods and tools used to collect and analyze data. It highlights the need for consistent data collection procedures and the use of advanced analytical techniques to derive meaningful insights from the data.

3. The third part of the document focuses on the implementation of data-driven decision-making processes. It discusses how the collected data is used to identify trends, assess risks, and make strategic decisions that align with the organization's goals and objectives.

4. The fourth part of the document addresses the challenges and limitations of data analysis. It acknowledges that while data provides valuable insights, it is not infallible and must be interpreted with care and context.

5. The fifth part of the document discusses the future of data analysis and the role of emerging technologies. It explores how artificial intelligence, machine learning, and big data are transforming the way organizations collect, analyze, and use data.

6. The sixth part of the document provides a summary of the key findings and conclusions. It reiterates the importance of data in driving organizational success and the need for a strong data governance framework.

7. The seventh part of the document offers recommendations for further research and action. It suggests areas where more data is needed and provides practical steps for improving data collection and analysis practices.

8. The eighth part of the document concludes with a final statement on the value of data. It emphasizes that data is not just a collection of numbers, but a powerful tool for understanding the world and making better decisions.